Flamco

Product Data Sheet (2018-10-18)

Airfix D-E-B - 16.0 bar

Standard vessels for use in all (potable) water installations. The construction also permits use in closed HVAC installations with a maximum temperature of 70 °C.

The composition of the bladder has been made for this range in such a way that there will be no variation in smell, colour or taste. The inside of the Airfix connection flange has a special coating which prevents oxidation.

Type	Capacity [l]	Dimensions Ø [mm]	Dimensions H. [mm]	Connection	Weight [kg]	###	Order Code
Airfix D-E-B 50	50	450	830	Rp 1 ½"	58	1	14703
Airfix D-E-B 80	80	450	1010	Rp 1 ½"	69	1	14803
Airfix D-E-B 120	120	450	1265	Rp 1 ½"	83	1	14815
Airfix D-E-B 180	180	550	1255	Rp 1 ½"	124	1	14821
Airfix D-E-B 240	240	550	1515	Rp 1 ½"	147	1	14827
Airfix D-E-B 300	300	550	1855	Rp 1 ½"	178	1	14833
Airfix D-E-B 600	600	750	1840	Rp 2"	282	1	14863
Airfix D-E-B 800	800	750	2230	Rp 2"	333	1	14883
Airfix D-E-B 1000	1000	750	2730	Rp 2"	398	1	14913
Airfix D-E-B 1600	1600	1000	2680	Rp 2 ½"	587	1	14919
Airfix D-E-B 2000	2000	1200	2400	Rp 2 ½"	657	1	14923
Airfix D-E-B 3000	3000	1200	3300	Rp 2 ½"	864	1	14933

WRAS APPROVED PRODUCT

CE

Warranty 5 Year

Advantages

- Nitrogen gas filling for longer retention of pre-charge.
- Replaceable butyl rubber bladder according to DIN4807/5.
- With single threaded coated steel connection (no flow-through function).

© 2018 Flamco B.V. All rights reserved. We reserve the right to change designs and technical specifications of our products.

Technical information

- Maximum working pressure: 16.0 bar.
- Standard pre-charge: 6.0 bar.
- Maximum working temperature (bladder): 70 °C.
- Colour: White, RAL 9010.
- In accordance with Pressure Equipment Directive 2014/68/EU.
- Material quality:

S235JR.
EN/ISO: P245N.

- 40 bar execution available on request.

Find more information online:

Manuals
Certificates
CAD drawings
Extra documentation

Flamco Group
Amersfoortseweg 9
3751 LJ, Bunschoten - nl
T +31 33 299 75 00
F +31 33 298 64 45
E info@flamcogroup.com
I flamcogroup.com

© 2018 Flamco B.V. All rights reserved. We reserve the right to change designs and technical specifications of our products.