

Jabsco Flexible Impeller Pump Head Kit

Model series	22860	22870	22880	22890	53270
Model numbers	22860-2001, 22860-2003, 22860-2021, 22860-2061, 22860-2702	22870-2001, 22870-2003, 22870-2043, 22870-2201, 22870-2203, 22870-2543, 22870-2702	22880-0033, 22880-2001, 22880-2003, 22880-2201, 22880-2203, 22880-2401	22890-2001	53270-2011, 53270-2013, 53270-2003
Flow rate at 1500 rpm	8.9 GPM (40 LPM)	17.8 GPM (80 LPM)	4.4 GPM (200 LPM)	60 GPM (270 LPM)	60 GPM (270 LPM)
Self-priming from dry	Up to 7.8 ft. (2.4m)	Up to 7.8 ft. (2.4m)	Up to 7.8 ft. (2.4m)	Up to 7.8 ft. (2.4m)	Up to 7.8 ft. (2.4m)
Body materials	Bronze	Bronze	Bronze	Bronze	Bronze
Pump / motor adapter	Epoxy-coated aluminium	Epoxy-coated aluminium	Epoxy-coated aluminium	Epoxy-coated aluminium	Epoxy-coated aluminium
Impeller	Neoprene or Nitrile	Neoprene or Nitrile	Neoprene or Nitrile	Neoprene	Neoprene or Nitrile
Seal	Carbon / ceramic mechanical seal	Carbon / ceramic mechanical seal	Carbon / ceramic mechanical seal	Carbon / ceramic mechanical seal	Carbon / ceramic mechanical seal
Bearings	Uses motor bearings	Uses motor bearings	Uses motor bearings	Uses motor bearings	Uses motor bearings
Shaft material	316 Stainless steel shaft extension	316 Stainless steel shaft extension	316 Stainless steel shaft extension	316 Stainless steel shaft extension	316 Stainless steel shaft extension
Port type	3/4" (19 mm) BSP internal thread to BS21 (DIN2999)	1" (25 mm) BSP internal thread to BS21 (DIN2999)	1 1/2" (38 mm) Flanged, BSP adapters included	2" (51 mm) Flanged, BSP adapters included	2" (51 mm) BSP internal thread to BS21 (DIN2999)
Weight	4.2 lb. (1.9 kg)	5.7 lb. (2.6 kg)	16.9 lb. (7.7 kg)	20.5 lb. (9.3 kg)	20.5 lb. (9.3 kg)