

**Jabsco Flange Mount
Flexible Impeller Pumps**

Model series	10970	17360	18400	18940	21140	29500	3270	43210
Model numbers	10970, 10970-21	17360-1001	18400-0050	18940-0010	21140-2401	29500-1001, 29500-1501, 29500-1901	3270-0001, 3270-200, 3270-2013, 3270-2201	43210-0001
Flow rate @ 1500 rpm	8.9 GPM (40 LPM)	60 GPM (270 LPM)	5.8 GPM (22 LPM)	8.9 GPM (40 LPM)	17.8 GPM (80 LPM)	8.9 GPM (40 LPM)	8.9 GPM (40 LPM)	20 GPM (75 LPM)
Self-priming from dry	Up to 7.8 ft. (2.4m)	Up to 7.8 ft. (2.4m)	Up to 7.8 ft. (2.4m)	Up to 7.8 ft. (2.4m)	Up to 7.8 ft. (2.4m)	Up to 7.8 ft. (2.4m)	Up to 7.8 ft. (2.4m)	N/A
Body materials	Bronze head, cast iron bearing housing	Bronze head, cast iron bearing housing	Bronze	Bronze	Bronze head, cast iron bearing housing	Bronze	Bronze	Bronze
Impeller	Neoprene	Neoprene	Neoprene	Neoprene	Neoprene	Neoprene	Neoprene	Neoprene
Shaft material	316 Stainless steel	Stainless steel	316 Stainless steel	Stainless steel	316 Stainless steel	Stainless steel	Stainless steel	Stainless steel
Seal	Carbon / ceramic mechanical type	Carbon / ceramic mechanical type	Lip type	Carbon / ceramic mechanical type	Carbon / ceramic mechanical type	Lip type	Lip type	Lip type
Bearings	Twin single row, ball type	Twin single row, ball type	Twin single row, ball type	Twin single row, ball type	Twin single row, ball type	Twin row, ball type	Twin row, ball type	Twin single row, ball type
Port type	3/4" (19mm) thread or flange	2 1/2" (63mm) flange	3/4" (19mm) NPT	1-1/4" (32mm) ID Hose	1" (25mm) BSP to BS21 (DIN2999)	1.1" (28mm) hose barb	3/4" (19mm) thread	1-1/4" (32mm) hose barb
Weight	7 lb. (3.2 kg)	28 lb. (12.7 kg)	6 lb. (2.7 kg)	7 lb. (3.2 kg)	8 lb. (3.6 kg)	2.5 lb. (1.2 kg)	4 lb. (1.8 kg)	7 lb. (3.2 kg)

**Jabsco Flange Mount
Flexible Impeller Pumps**

Model series	50410	5850	9700	9970	10950
Model numbers	50410-1201, 50410-1251, 50410-1301, 50410-1351, 50410-1401	5850-0001	9700-01, 9700-0001, 9700-04, 9700-131, 9700-131	9970-200, 9970-241, 9970-241-37	10950-2401
Flow rate @ 1500 rpm	14 GPM (53 LPM)	10.6 GPM (40 LPM)	17.8 GPM (80 LPM)	8.9 GPM (40 LPM)	Engine dependant
Self-priming from dry	Up to 7.8 ft. (2.4m)	Up to 7.8 ft. (2.4m)	Up to 7.8 ft. (2.4m)	Up to 7.8 ft. (2.4m)	Engine dependant
Body materials	Bronze	Bronze	Bronze	Bronze	Bronze
Impeller	Neoprene	Neoprene	Neoprene	Neoprene	Neoprene
Shaft material	316 Stainless steel	316 Stainless steel	316 Stainless steel	316 Stainless steel	316 Stainless steel
Seal	Lip type or carbon / ceramic mechanical type	Lip type	Carbon / ceramic mechanical type	Carbon / ceramic mechanical type	Carbon / ceramic mechanical type
Bearings	Single row, ball type	Twin single row, ball type	Twin row, ball type	Twin single row, ball type	Twin single row, ball type
Port type	1-1/4" (32mm) hose barb	3/4" (19mm) NPT	1" (25mm) flange	3/4" (19mm) BSP to BS21 (DIN2999)	3/4" (19mm) BSP to BS21 (DIN2999)
Weight	5 lb. (2.2 kg)	6 lb. (2.7 kg)	6 lb. (2.8 kg)	4 lb. (1.8 kg)	7 lb. (3.2 kg)