

**Jabsco Pedestal Flexible
Impeller Pumps**

Model series	10550	1673	18370	2620	2760	29860	3890	42730
Model numbers	10550-200	1673-1001, 1673-1003, 1673-2001	18370-0000	2620-1101, 2620-1103	2760-0001, 2760-0003	29860-2201	3890-9011	42730-0000
Flow rate @ 1500 rpm	8.9 GPM (40 LPM)	8.9 GPM (40 LPM)	60 GPM (270 LPM)	4.4 GPM (20 LPM)	4.4 GPM (20 LPM)	110 GPM (500 LPM)	10.6 GPM (40 LPM)	12 GPM (54 LPM)
Self-priming from dry	Up to 18 ft. (5.6m)	Up to 7.8 ft. (2.4m)	Up to 7.8 ft. (2.4m)	Up to 4.9 ft. (1.5m)	Up to 4.9 ft. (1.5m)	Up to 7.8 ft. (2.4m)	Up to 7.8 ft. (2.4m)	Up to 7.8 ft. (2.4m)
Body materials	Bronze	Bronze	Bronze	Bronze	Bronze	Bronze	Bronze	Bronze
Impeller	Neoprene	Neoprene or Nitrile	Neoprene or Nitrile	Neoprene or Nitrile	Neoprene or Nitrile	Neoprene	Neoprene	Neoprene
Shaft material	Stainless steel	Stainless steel	Stainless steel	Type 316 Stainless steel	Stainless steel	Stainless steel	Stainless steel	Stainless steel
Seal	Carbon / ceramic mechanical type	Lip Seal, Nitrile	Carbon / ceramic mechanical type	Nitrile lip type	Lip type	Carbon / ceramic mechanical type	Carbon / ceramic mechanical type	Carbon / ceramic mechanical type
Bearings	Twin single row, ball type	Sealed ball bearings	Twin single row, ball type	Sealed ball bearings	Sealed ball bearings	Twin single row, ball type	Twin row, ball type	Twin single row, ball type
Port type	3/4" (19mm) BSP thread	1/2" (13mm) NPT	2" (51mm) NPT Internal	3/8" (9mm) NPT(f) Internal	1/4" (6mm) Internal thread	2 1/2" (63mm) Flange and BSP to BS21 (DIN2999)	3/4" (19mm) NPT	1" (25mm) NPT
Weight	7 lb. (3 kg)	4.25 lb. (2 kg)	19 lb. (8.6 kg)	2.75 lb. (1.3 kg)	1.5 lb. (0.7 kg)	27.5 lb. (12.5 kg)	4 lb. (1.8 kg)	8 lb. (3.6 kg)

**Jabsco Pedestal Flexible
Impeller Pumps**

Model series	51510	51520	52040	52080	52200	52220	52270	52580
Model numbers	51510-2001, 51510-9001	51520-2001, 51520-9001	52040-2001, 52040-2003, 52040-2021	52080-2001, 52080-2003, 52080-2021	52200-2011, 52200-2003, 52200-2021, 52200-9011	52220-0011, 52220-0021	52270-0011, 52270-2011	52580-2001
Flow rate @ 1500 rpm	2.2 GPM (10 LPM)	4.4 GPM (20 LPM)	8.9 GPM (40 LPM)	17.8 GPM (80 LPM)	44.5 GPM (200 LPM)	44.5 GPM (200 LPM)	60 GPM (270 LPM)	17.8 GPM (80 LPM)
Self-priming from dry	Up to 4.9 ft. (1.5m)	Up to 4.9 ft. (1.5m)	Up to 7.8 ft. (2.4m)	Up to 7.8 ft. (2.4m)	Up to 7.8 ft. (2.4m)	Up to 7.8 ft. (2.4m)	Up to 7.8 ft. (2.4m)	Up to 7.8 ft. (2.4m)
Body materials	Brass	Brass	Bronze	Bronze	Bronze	Bronze head, cast iron bearing housing	Bronze head, cast iron bearing housing	Bronze
Impeller	Neoprene	Neoprene	Neoprene or Nitrile	Neoprene or Nitrile	Neoprene or Nitrile	Neoprene or Nitrile	Neoprene or Nitrile	Neoprene or Nitrile
Shaft material	Stainless steel	Stainless steel	Stainless steel	Stainless steel	Stainless steel	Stainless steel	Stainless steel	Stainless steel
Seal	Carbon / ceramic mechanical	Carbon / ceramic mechanical	Lip type	Lip type	Carbon / ceramic mechanical	Carbon / ceramic mechanical	Carbon / ceramic mechanical	Carbon / ceramic mechanical
Bearings	Sealed ball bearings	Sealed ball bearings	Twin row, ball type	Twin row, ball type	Twin row, ball type	Twin single row, ball type	Twin single row, ball type	Twin single row, ball type
Port type	3/8" (9mm) BSP or 3/8" (9mm) NPT	3/8" (9mm) BSP or 3/8" (9mm) NPT	3/4" (19mm) BSP to BS21 (DIN2999)	1" (25mm) BSP to BS21 (DIN2999)	1 1/2" (38mm) BSP to BS21 (DIN2999)	1 1/2" (38mm) Flange	2" (51mm) Flanged or 2" (51mm) BSP to BS21 (DIN2999)	1" (25mm) BSP to BS21 (DIN2999) or NPT
Weight	1.4 lb. (0.6 kg)	1.5 lb. (0.7 kg)	3.3 lb. (1.5 kg)	4.6 lb. (2.1 kg)	11 lb. (5 kg)	15.4 lb. (7 kg)	19.8 lb. (9 kg)	7.3 lb. (3.3 kg)

**Jabsco Pedestal Flexible
Impeller Pumps**

Model series	6400	7420	777	9710	5320	5330
Model numbers	6400-0004, 6400-0051, 6400-1001, 6400-1051, 6400-1551	7420-0004, 7420-0101, 7420-1001, 7420-1501	777-0001, 777-0003, 777-9001, 777-9003, 777-9051	9710-200, 9710-2103	5320-0011	5330-9001
Flow rate @ 1500 rpm	44.4 GPM (200 LPM)	44.4 GPM (200 LPM)	17.8 GPM (80 LPM)	17.8 GPM (80 LPM)	5.8 GPM (22 LPM)	26 GPM (98 LPM)
Self-priming from dry	Up to 7.8 ft. (2.4m)	Up to 7.8 ft. (2.4m)	Up to 7.8 ft. (2.4m)	Up to 7.8 ft. (2.4m)	Up to 10ft (3m)	Up to 10ft (3m)
Body materials	Bronze	Bronze	Bronze	Bronze head, cast iron bearing housing	Bronze	Bronze
Impeller	Neoprene or Nitrile	Neoprene or Nitrile	Neoprene or Nitrile	Neoprene or Nitrile	Neoprene	Nitrile
Shaft material	Type 316 stainless steel	Type 316 stainless steel	Stainless steel	Stainless steel	Stainless steel	Stainless steel
Seal	Carbon- ceramic face type	Carbon- ceramic face type	Mechanical face seal or lip type	Carbon / ceramic mechanical type	Lip type	Carbon / ceramic mechanical type
Bearings	Pre-lubricated double row ball	Pre-lubricated double row ball	Shielded ball bearings	Twin single row, ball type	Twin single row, ball type	Double row ball bearing
Port type	1-1/4" (32mm) NPT Internal	1-1/4" (32mm) NPT Internal	1" (25mm) NPT	1" (25mm) BSP to BS21 (DIN2999)	3/8" (9mm) NPT	1" (25mm) NPT
Weight	10.5 lb. (4.8 kg)	10.5 lb. (4.8 kg)	5.75 lb. (2.6 kg)	7.8 lb. (3.6 kg)	1.5 lb. (0.7 kg)	7 lb. (3.2 kg)