

TRIPLEX SERIES

| PUMP TYPE     | MODEL #   | CE        | MOTOR TYPE                             | VOLTAGE   | AMP DRAW  | PUMP HEAD                  | ELASTOMERS                         | FLOW RATE                      | PRESSURE SWITCH      | BYPASS           |
|---------------|-----------|-----------|--|-----------|-----------|----------------------------|------------------------------------|--------------------------------|----------------------|------------------|
| Road Roller   | na        | R3B21501A | Permanent magnet DC                    | 24 Volt   | 5 (amp)   | Glass-filled Polypropylene | Santoprene diaphragm, Viton valves | 3.5 GPM (13.2 LPM) - Open Flow | No                   | 50 psi (3.4 bar) |
| Road Roller   | na        | R3B21502A | Permanent magnet DC                    | 12 Volt   | 4 (amp)   | Glass-filled Polypropylene | Santoprene diaphragm, Viton valves | 2.1 GPM (7.9 LPM) - Open Flow  | No                   | 50 psi (3.4 bar) |
| Road Roller   | na        | R3B21503A | Permanent magnet DC                    | 24 Volt   | 4 (amp)   | Glass-filled Polypropylene | Santoprene diaphragm, Viton valves | 2.1 GPM (7.9 LPM) - Open Flow  | No                   | 50 psi (3.4 bar) |
| Compact       | na        | R3501132  | Permanent Magnet TENV (non-ventilated) | 12 (Vdc)  | 6 (amp)   | Glass-filled Polypropylene | Santoprene diaphragm, Viton valves | 1.4 GPM (5.3 LPM) - Open Flow  | 60 psi (4.1 bar)     | 40 psi (2.8 bar) |
| Compact       | na        | R3501136  | Permanent Magnet TENV (non-ventilated) | 12 (Vdc)  | 8 (amp)   | Glass-filled Polypropylene | Santoprene diaphragm, Viton valves | 2.0 GPM (7.9 LPM) - Open Flow  | 60 psi (4.1 bar)     | 40 psi (2.8 bar) |
| Compact       | na        | R3501142  | Permanent Magnet TENV (non-ventilated) | 12 (Vdc)  | 6 (amp)   | Glass-filled Polypropylene | Santoprene diaphragm, EPDM valves  | 1.4 GPM (5.3 LPM) - Open Flow  | 60 psi (4.1 bar)     | 40 psi (2.8 bar) |
| Compact       | na        | R3501146  | Permanent Magnet TENV (non-ventilated) | 12 (Vdc)  | 8 (amp)   | Glass-filled Polypropylene | Santoprene diaphragm, EPDM valves  | 2.0 GPM (7.9 LPM) - Open Flow  | 60 psi (4.1 bar)     | 40 psi (2.8 bar) |
| Compact       | na        | R3501332  | Permanent Magnet TENV (non-ventilated) | 24 (Vdc)  | 3 (amp)   | Glass-filled Polypropylene | Santoprene diaphragm, Viton valves | 1.4 GPM (5.3 LPM) - Open Flow  | 60 psi (4.1 bar)     | 40 psi (2.8 bar) |
| Compact       | na        | R3501336  | Permanent Magnet TENV (non-ventilated) | 24 (Vdc)  | 4 (amp)   | Glass-filled Polypropylene | Santoprene diaphragm, Viton valves | 2.0 GPM (7.9 LPM) - Open Flow  | 60 psi (4.1 bar)     | 40 psi (2.8 bar) |
| Compact       | na        | R3501342  | Permanent Magnet TENV (non-ventilated) | 24 (Vdc)  | 3 (amp)   | Glass-filled Polypropylene | Santoprene diaphragm, EPDM valves  | 1.4 GPM (5.3 LPM) - Open Flow  | 60 psi (4.1 bar)     | 40 psi (2.8 bar) |
| Compact       | na        | R3501346  | Permanent Magnet TENV (non-ventilated) | 24 (Vdc)  | 4 (amp)   | Glass-filled Polypropylene | Santoprene diaphragm, EPDM valves  | 2.0 GPM (7.9 LPM) - Open Flow  | 60 psi (4.1 bar)     | 40 psi (2.8 bar) |
| Compact       | 03501503  | na        | Permanent Magnet TENV (non-ventilated) | 12 (Vdc)  | 8 (amp)   | Glass-filled Polypropylene | Santoprene diaphragm, Viton valves | 2.0 GPM (7.9 LPM) - Open Flow  | 60 psi (4.1 bar)     | Yes              |
| Compact       | 03501506  | na        | Permanent Magnet TENV (non-ventilated) | 12 (Vdc)  | 8 (amp)   | Glass-filled Polypropylene | Santoprene diaphragm, Viton valves | 2.0 GPM (7.9 LPM) - Open Flow  | 60 psi (4.1 bar)     | Yes              |
| Compact       | 03B01136  | R3B01136  | Permanent Magnet TENV (non-ventilated) | 12 (Vdc)  | 8 (amp)   | Glass-filled Polypropylene | Santoprene diaphragm, Viton valves | 2.0 GPM (7.9 LPM) - Open Flow  | No                   | 50 psi (3.4 bar) |
| Compact       | 03B01142  | R3B01142  | Permanent Magnet TENV (non-ventilated) | 12 (Vdc)  | 6 (amp)   | Glass-filled Polypropylene | Santoprene diaphragm, EPDM valves  | 1.4 GPM (5.3 LPM) - Open Flow  | No                   | 50 psi (3.4 bar) |
| Compact       | na        | R3B01332  | Permanent Magnet TENV (non-ventilated) | 24 (Vdc)  | 3 (amp)   | Glass-filled Polypropylene | Santoprene diaphragm, Viton valves | 1.4 GPM (5.3 LPM) - Open Flow  | No                   | 50 psi (3.4 bar) |
| Compact       | na        | R3B01342  | Permanent Magnet TENV (non-ventilated) | 24 (Vdc)  | 3 (amp)   | Glass-filled Polypropylene | Santoprene diaphragm, EPDM valves  | 1.4 GPM (5.3 LPM) - Open Flow  | No                   | 50 psi (3.4 bar) |
| High Flow     | na        | R3521134  | Permanent magnet DC                    | 12 (Vdc)  | 5.2 (amp) | Glass-filled Polypropylene | Santoprene diaphragm, Viton valves | 3.0 GPM (11.3 LPM) - Open Flow | 50 psi (3.4 bar)     | 30 psi (2.0 bar) |
| High Flow     | 3521139   | R3521139  | Permanent magnet DC                    | 12 (Vdc)  | 12 (amp)  | Glass-filled Polypropylene | Santoprene diaphragm, Viton valves | 4.0 GPM (15.1 LPM) - Open Flow | 60 PSI (4.1 bar)     | 30 psi (2.0 bar) |
| High Flow     | 3521149   | R3521149  | Permanent magnet DC                    | 12 (Vdc)  | 12 (amp)  | Glass-filled Polypropylene | Santoprene diaphragm, EPDM valves  | 4.0 GPM (15.1 LPM) - Open Flow | 60 psi (4.1 bar)     | 30 psi (2.0 bar) |
| High Flow     | na        | R3521339  | Permanent magnet DC                    | 24 (Vdc)  | 7 (amp)   | Glass-filled Polypropylene | Santoprene diaphragm, Viton valves | 4.0 GPM (15.1 LPM) - Open Flow | 60 psi (4.1 bar)     | 30 psi (2.0 bar) |
| High Flow     | na        | R3521344  | Permanent magnet DC                    | 24 (Vdc)  | 2.5 (amp) | Glass-filled Polypropylene | Santoprene diaphragm, EPDM valves  | 3.0 GPM (11.3 LPM) - Open Flow | 50 psi (3.4 bar)     | 30 psi (2.0 bar) |
| High Flow     | na        | R3521349  | Permanent magnet DC                    | 24 (Vdc)  | 7 (amp)   | Glass-filled Polypropylene | Santoprene diaphragm, EPDM valves  | 4.0 GPM (15.1 LPM) - Open Flow | 60 psi (4.1 bar)     | 30 psi (2.0 bar) |
| High Pressure | 03811133A | R3811133A | Permanent magnet TENV (non-ventilated) | 12 (Vdc)  | 10 (amp)  | Glass-filled Nylon         | Santoprene Diaphragm, Viton Valves | 1.4 GPM (5.3 LPM) - Open Flow  | 150 (psi) 10.5 (bar) | No               |
| High Pressure | 03811143A | R3811143A | Permanent magnet TENV (non-ventilated) | 12 (Vdc)  | 10 (amp)  | Glass-filled Nylon         | Santoprene Diaphragm, EPDM Valves  | 1.4 GPM (5.3 LPM) - Open Flow  | 150 (psi) 10.5 (bar) | No               |
| High Pressure | na        | R3811233A | Permanent magnet TENV (non-ventilated) | 230 (VAC) | 0.6 (amp) | Glass-filled Nylon         | Santoprene Diaphragm, Viton Valves | 1.4 GPM (5.3 LPM) - Open Flow  | 150 (psi) 10.5 (bar) | No               |
| High Pressure | 03811243A | R3811243A | Permanent magnet TENV (non-ventilated) | 230 (VAC) | 0.6 (amp) | Glass-filled Nylon         | Santoprene Diaphragm, EPDM Valves  | 1.4 GPM (5.3 LPM) - Open Flow  | 150 (psi) 10.5 (bar) | No               |

**TRIPLEX SERIES**

| PUMP TYPE     | MODEL #   | CE        | MAX LIQUID TEMP            | DUTY CYCLE   | DIMENSIONS (H x W x D)                                  | WEIGHT              | CERTIFICATION            | PORT SIZE INLET / OUTLET |
|---------------|-----------|-----------|----------------------------|--------------|---|---------------------|--------------------------|--------------------------|
| Road Roller   | na        | R3B21501A | 40°F (4°C) to 140°F (60°C) | Intermittent | 9.53 x 4.45 x 4.24 (inches)<br>242.1 x 113 x 107.7 (mm) | 3.17 (kg) 7.0 (lb)  | CE, RoHS, C-Tick, E-Mark | Quick-Connect Ports      |
| Road Roller   | na        | R3B21502A | 40°F (4°C) to 140°F (60°C) | Intermittent | 9.53 x 4.45 x 4.24 (inches)<br>242.1 x 113 x 107.7 (mm) | 3.17 (kg) 7.0 (lb)  | CE, RoHS, C-Tick, E-Mark | Quick-Connect Ports      |
| Road Roller   | na        | R3B21503A | 40°F (4°C) to 140°F (60°C) | Intermittent | 9.53 x 4.45 x 4.24 (inches)<br>242.1 x 113 x 107.7 (mm) | 3.17 (kg) 7.0 (lb)  | CE, RoHS, C-Tick, E-Mark | Quick-Connect Ports      |
| Compact       | na        | R3501132  | 40°F (4°C) to 140°F (60°C) | Intermittent | 8.92 x 3.66 x 3.96 (inches) 227<br>x 93 x 101 (mm)      | 1.5 (kg) 3.4 (lb)   | CE, NSF components       | 3/8" NPTF                |
| Compact       | na        | R3501136  | 40°F (4°C) to 140°F (60°C) | Intermittent | 8.92 x 3.66 x 3.96 (inches) 227<br>x 93 x 101 (mm)      | 1.5 (kg) 3.4 (lb)   | CE, NSF components       | 3/8" NPTF                |
| Compact       | na        | R3501142  | 40°F (4°C) to 140°F (60°C) | Intermittent | 8.92 x 3.66 x 3.96 (inches) 227<br>x 93 x 101 (mm)      | 1.5 (kg) 3.4 (lb)   | CE, NSF components       | 3/8" NPTF                |
| Compact       | na        | R3501146  | 40°F (4°C) to 140°F (60°C) | Intermittent | 8.92 x 3.66 x 3.96 (inches) 227<br>x 93 x 101 (mm)      | 1.5 (kg) 3.4 (lb)   | CE, NSF components       | 3/8" NPTF                |
| Compact       | na        | R3501332  | 40°F (4°C) to 140°F (60°C) | Intermittent | 8.92 x 3.66 x 3.96 (inches) 227<br>x 93 x 101 (mm)      | 1.5 (kg) 3.4 (lb)   | CE, NSF components       | 3/8" NPTF                |
| Compact       | na        | R3501336  | 40°F (4°C) to 140°F (60°C) | Intermittent | 8.92 x 3.66 x 3.96 (inches) 227<br>x 93 x 101 (mm)      | 1.5 (kg) 3.4 (lb)   | CE, NSF components       | 3/8" NPTF                |
| Compact       | na        | R3501342  | 40°F (4°C) to 140°F (60°C) | Intermittent | 8.92 x 3.66 x 3.96 (inches) 227<br>x 93 x 101 (mm)      | 1.5 (kg) 3.4 (lb)   | CE, NSF components       | 3/8" NPTF                |
| Compact       | na        | R3501346  | 40°F (4°C) to 140°F (60°C) | Intermittent | 8.92 x 3.66 x 3.96 (inches) 227<br>x 93 x 101 (mm)      | 1.5 (kg) 3.4 (lb)   | CE, NSF components       | 3/8" NPTF                |
| Compact       | 03501503  | na        | 40°F (4°C) to 140°F (60°C) | Intermittent | 8.92 x 3.66 x 3.96 (inches) 227<br>x 93 x 101 (mm)      | 1.5 (kg) 3.4 (lb)   | CE, NSF components       | 3/8" NPTF                |
| Compact       | 03501506  | na        | 40°F (4°C) to 140°F (60°C) | Intermittent | 8.92 x 3.66 x 3.96 (inches) 227<br>x 93 x 101 (mm)      | 1.5 (kg) 3.4 (lb)   | CE, NSF components       | 3/8" NPTF                |
| Compact       | 03B01136  | R3B01136  | 40°F (4°C) to 140°F (60°C) | Intermittent | 8.92 x 3.66 x 3.96 (inches) 227<br>x 93 x 101 (mm)      | 1.5 (kg) 3.4 (lb)   | CE, NSF components       | 3/8" NPTF                |
| Compact       | 03B01142  | R3B01142  | 40°F (4°C) to 140°F (60°C) | Intermittent | 8.92 x 3.66 x 3.96 (inches) 227<br>x 93 x 101 (mm)      | 1.5 (kg) 3.4 (lb)   | CE, NSF components       | 3/8" NPTF                |
| Compact       | na        | R3B01332  | 40°F (4°C) to 140°F (60°C) | Intermittent | 8.92 x 3.66 x 3.96 (inches) 227<br>x 93 x 101 (mm)      | 1.5 (kg) 3.4 (lb)   | CE, NSF components       | 3/8" NPTF                |
| Compact       | na        | R3B01342  | 40°F (4°C) to 140°F (60°C) | Intermittent | 8.92 x 3.66 x 3.96 (inches) 227<br>x 93 x 101 (mm)      | 1.5 (kg) 3.4 (lb)   | CE, NSF components       | 3/8" NPTF                |
| High Flow     | na        | R3521134  | 40°F (4°C) to 140°F (60°C) | Intermittent | 9.06 x 4.14 x 4.30 (inches) 230<br>x 105 x 109 (mm)     | 2.29 (kg) 5.05 (lb) | CE                       | Quick-Connect Ports      |
| High Flow     | 3521139   | R3521139  | 40°F (4°C) to 140°F (60°C) | Intermittent | 9.06 x 4.14 x 4.30 (inches) 230<br>x 105 x 109 (mm)     | 2.29 (kg) 5.05 (lb) | CE                       | Quick-Connect Ports      |
| High Flow     | 3521149   | R3521149  | 40°F (4°C) to 140°F (60°C) | Intermittent | 9.06 x 4.14 x 4.30 (inches) 230<br>x 105 x 109 (mm)     | 2.29 (kg) 5.05 (lb) | CE                       | Quick-Connect Ports      |
| High Flow     | na        | R3521339  | 40°F (4°C) to 140°F (60°C) | Intermittent | 9.06 x 4.14 x 4.30 (inches) 230<br>x 105 x 109 (mm)     | 2.29 (kg) 5.05 (lb) | CE                       | Quick-Connect Ports      |
| High Flow     | na        | R3521344  | 40°F (4°C) to 140°F (60°C) | Intermittent | 9.06 x 4.14 x 4.30 (inches) 230<br>x 105 x 109 (mm)     | 2.29 (kg) 5.05 (lb) | CE                       | Quick-Connect Ports      |
| High Flow     | na        | R3521349  | 40°F (4°C) to 140°F (60°C) | Intermittent | 9.06 x 4.14 x 4.30 (inches) 230<br>x 105 x 109 (mm)     | 2.29 (kg) 5.05 (lb) | CE                       | Quick-Connect Ports      |
| High Pressure | 03811133A | R3811133A | 40°F (4°C) to 140°F (60°C) | Intermittent | 10.7 x 3.18 x 3.67 (inches) 256<br>x 80 x 93 (mm)       | 3.5 (kg) 7.6 (lb)   | CE, NSF components       | 3/8" NPTF                |
| High Pressure | 03811143A | R3811143A | 40°F (4°C) to 140°F (60°C) | Intermittent | 10.7 x 3.18 x 3.67 (inches) 256<br>x 80 x 93 (mm)       | 3.5 (kg) 7.6 (lb)   | CE, NSF components       | 3/8" NPTF                |
| High Pressure | na        | R3811233A | 40°F (4°C) to 140°F (60°C) | Intermittent | 10.7 x 3.18 x 3.67 (inches) 256<br>x 80 x 93 (mm)       | 3.5 (kg) 7.6 (lb)   | CE, NSF components       | 3/8" NPTF                |
| High Pressure | 03811243A | R3811243A | 40°F (4°C) to 140°F (60°C) | Intermittent | 10.7 x 3.18 x 3.67 (inches) 256<br>x 80 x 93 (mm)       | 3.5 (kg) 7.6 (lb)   | CE, NSF components       | 3/8" NPTF                |